

## **TECHNICAL DATA SHEET**

Revision: 3

Edition: June/2024

### **STANLUX FLAKE 4300**

- Aluminium powder in lamellar form
- Leafing grade with coarse particles

#### ***SPECIFIED CHARACTERISTICS***

- |                                   |                          |
|-----------------------------------|--------------------------|
| • Maximum retention in # 325 Mesh | 20.0%                    |
| • Minimum water coverage          | 7,000 cm <sup>2</sup> /g |

#### ***INFORMATIVE CHARACTERISTICS***

- |   |            |
|---|------------|
| • Average Particles Size- (D50 – Malvern) | 35 microns |
| • Minimum solid content                   | 97%        |

#### ***Typical Uses***

- Plastics
- Explosives
- Pyrotechnic
- Pesticide formulations

---

Before using the product, we recommend that you consult the safety information, including the adequate handling and transport, which are available in the product's Material Safety Data Sheet – MSDS. The information mentioned in this technical bulletin represents our current level of knowledge and experience, but shall not be considered as a guarantee. It is the user's responsibility to assure the adequate use of the product, since **Aldoro** will not accept liability on any type of loss or damage which may arise due to the use of this information or application of the product. **Aldoro** reserves itself the right of changing, without prior notice, any data contained in this bulletin, resulting from adjustment, development or evolution of the production process.

---