

## **TECHNICAL DATA SHEET**

Revision: 6

Edition: June/2024

### **STANLUX FLAKE CL 4010**

- Special aluminium powder in lamellar form for light weight concrete

#### ***SPECIFIED CHARACTERISTICS***

- |                                   |                               |
|-----------------------------------|-------------------------------|
| • Minimum active metal            | 92%                           |
| • Density                         | 0.12 - 0.15 g/cm <sup>3</sup> |
| • Maximum retention in # 325 Mesh | 5.0%                          |

#### ***INFORMATIVE CHARACTERISTICS***

- |   |            |
|---|------------|
| • Average Particles Size- (D50 - Malvern) | 16 microns |
| • Minimum solid content                   | 97%        |

#### ***Typical Uses***

- Light weight concrete

---

Before using the product, we recommend that you consult the safety information, including the adequate handling and transport, which are available in the product's Material Safety Data Sheet – MSDS. The information mentioned in this technical bulletin represents our current level of knowledge and experience, but shall not be considered as a guarantee. It is the user's responsibility to assure the adequate use of the product, since **Aldoro** will not accept liability on any type of loss or damage which may arise due to the use of this information or application of the product. **Aldoro** reserves itself the right of changing, without prior notice, any data contained in this bulletin, resulting from adjustment, development or evolution of the production process.

---