

## **TECHNICAL DATA SHEET**

Revision: 2

Edition: June/2024

### **STANLUX PELL 270 R**

- Pelletized aluminium pigment with Universal Resin in composition.
- Fine particles size, with lamellar shape and leafing type.
- This grade offers advantage of clean handling and process during its application in printing ink for flexographic and gravure.

#### ***SPECIFIED CHARACTERISTICS***

- |                                       |                |
|---------------------------------------|----------------|
| • Solid content                       | 99,2% minimum  |
| • Universal Resin                     | 15,0 % approx. |
| • Maximum retention in # 325 Mesh (*) | 0,1 % maximum  |

#### ***INFORMATIVE CHARACTERISTICS***

- |  |            |
|--|------------|
| • Average Particles Size (D50 – Malvern) | 11 microns |
|--|------------|

#### ***Typical Uses***

- Printing ink for flexography and gravure.

(\*)- The information refers to the paste batch used to produce the pellet.

---

Before using the product, we recommend that you consult the safety information, including the adequate handling and transport, which are available in the product's Material Safety Data Sheet – MSDS. The information mentioned in this technical bulletin represents our current level of knowledge and experience, but shall not be considered as a guarantee. It is the user's responsibility to assure the adequate use of the product, since **Aldoro** will not accept liability on any type of loss or damage which may arise due to the use of this information or application of the product. **Aldoro** reserves itself the right of changing, without prior notice, any data contained in this bulletin, resulting from adjustment, development or evolution of the production process.

---