

TECHNICAL DATA SHEET

Revision: 3

Edition: June/2024

STANLUX PELL 280 RN

- Pelletized aluminium pigment with Universal Resin in composition.
- Fine particles size, with lenticular shape and non-leaving type.
- This grade offers advantage of clean handling and process during its application in printing ink for flexographic and gravure.

SPECIFIED CHARACTERISTICS

- | | |
|---------------------------------------|----------------|
| • Solid content | 99,2% minimum |
| • Universal Resin | 15,0 % approx. |
| • Maximum retention in # 325 Mesh (*) | 0,1 % maximum |

INFORMATIVE CHARACTERISTICS

- | | |
|--|------------|
| • Average Particles Size (D50 – Malvern) | 11 microns |
|--|------------|

Typical Uses

- Printing ink for flexography and gravure.

(*)- The information refers to the paste batch used to produce the pellet.

Before using the product, we recommend that you consult the safety information, including the adequate handling and transport, which are available in the product's Material Safety Data Sheet – MSDS. The information mentioned in this technical bulletin represents our current level of knowledge and experience, but shall not be considered as a guarantee. It is the user's responsibility to assure the adequate use of the product, since **Aldoro** will not accept liability on any type of loss or damage which may arise due to the use of this information or application of the product. **Aldoro** reserves itself the right of changing, without prior notice, any data contained in this bulletin, resulting from adjustment, development or evolution of the production process.
