

TECHNICAL DATA SHEET

Revision: 1

Edition: June/2024

STANLUX SILVER 3895

- High performance aluminium paste with lamellar particles
- Thin product with high coverage
- Especially recommended for use in high-performance systems requiring distinctive metallic effects
- Solvent: mixture of White Spirit and High Aromatic

SPECIFIED CHARACTERISTICS

- | | |
|-----------------------------------|------------|
| • Solid content | 63% to 67% |
| • Maximum retention in # 325 Mesh | 0.1% |
| • Maximum water content | 0,15% |

INFORMATIVE CHARACTERISTICS

- | | |
|--|--------------------------|
| • Average Particles Size (D50 - Malvern) | 13 microns approximately |
|--|--------------------------|

Typical Uses

- Automotive coatings systems – refinishing and car parts.
- Plastic coatings mainly for finishing electronics.
- Coatings that require a high metallic effect.

Before using the product, we recommend that you consult the safety information, including the adequate handling and transport, which are available in the product's Material Safety Data Sheet – MSDS. The information mentioned in this technical bulletin represents our current level of knowledge and experience, but shall not be considered as a guarantee. It is the user's responsibility to assure the adequate use of the product, since **Aldoro** will not accept liability on any type of loss or damage which may arise due to the use of this information or application of the product. **Aldoro** reserves itself the right of changing, without prior notice, any data contained in this bulletin, resulting from adjustment, development or evolution of the production process.
